

srfi-29 egg

Provides SRFI-29.
Extension for Chicken Scheme
Version 1.3

Kon Lovett

Table of Contents

1	About this egg	1
1.1	Version history	1
1.2	Requirements	1
1.3	Usage	1
2	Documentation	2
2.1	Extensions to SRFI-29	2
3	Issues	3
4	License	4
	Index	5

1 About this egg

1.1 Version history

- 1.3 Exports
- 1.2 Faster lookup
- 1.1 Added deletion procedures
- 1.0 Initial release

1.2 Requirements

This egg requires the following extensions:

`lookup-table`, `miscmacros`, `locale`, `chicken-2.223+`

1.3 Usage

Load this egg like so:

```
(require-extension srfi-29)
```

2 Documentation

srfi-29 is a CHICKEN port of SRFI-29.

This package largely follows the specification of SRFI-29. For more information see the documentation for [SRFI-29](#).

Bundles are assumed stored in the system bundle directory, (repository-path) "srfi-29-bundles". Within a bundle directory the structure is [(language) [(country)]] (module).

The default language is 'en. The default country is 'us. The locale package will override these if a locale is set. Otherwise the user must set the corresponding parameters.

2.1 Extensions to SRFI-29

The `store-bundle` and `load-bundle!` procedures accept an optional string directory path as the second argument, overriding the system bundle directory.

The `localized-template` procedure accepts a string object for the `template-name`.

All filesystem operations are assumed to succeed. Otherwise an error condition is raised.

`reset-locale-parameters` [procedure]
 (`reset-locale-parameters`)

If you change current-locale (see the locale egg documentation), you don't have to set the current-language and current-country parameters, you can simply call this procedure, and it will update those parameters to the values in the new locale. (Reset as in set anew.)

`undecclare-bundle!` [procedure]
 (`undecclare-bundle!` BUNDLE-SPECIFIER)

Removes the bundle specified by BUNDLE-SPECIFIER from the active bundles.

`remove-bundle!` [procedure]
 (`remove-bundle!` BUNDLE-SPECIFIER [ALTERNATE-DIR])

Removes the bundle specified by BUNDLE-SPECIFIER from the active bundles, and from the filesystem. The bundle directory is ALTERNATE-DIR, unless missing. Then the system bundle directory is used.

Will not remove the language [country] directory hierarchy created by `store-bundle!`.

3 Issues

Possible race condition creating a bundle file or directory.

current-locale-details is ill-defined, which symbol means what? This implementation defines details as a 3 element list, (script codeset modifier), where a missing element is indicated by #f.

The locale symbols must have a lowercase printname! As such they do not truly reflect ISO 639-1/2 & ISO 3166-1 standard names.

The locale details are ignored if part of a bundle specifier.

4 License

Copyright (c) 2005, Kon Lovett. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ASIS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Index

R

remove-bundle! 2

reset-locale-parameters 2

U

undeclare-bundle! 2